

DECLARATION OF PERFORMANCE

RA-423-V01-25

1. Product type:	423 Parkettfuge																																
2. Identification number:	Batch number, see product packaging																																
3. Intended use:	Facades, type 15651-1 F25HM EXT-INT-CC																																
4. Manufacturer:	Ramsauer GmbH & Co KG Alte Bundesstraße 147, A-5350 Strobl																																
5. Authorised officer:	-																																
6. Evaluation system for consistency of performance:	3 plus 3																																
7. Harmonised standard:	DIN EN ISO: 15651-1:2012-09																																
8. Notified body:	As a notified test laboratory, ift Rosenheim NB no. 0757 carried out the initial test using conformity system 3 and issued the test and classification reports																																
9. Essential properties:	<table border="1" data-bbox="146 1033 1452 1832"> <thead> <tr> <th>Essential property</th> <th>Performance</th> <th>Harmonised technical specification</th> </tr> </thead> <tbody> <tr> <td>Fire behaviour</td> <td>Class E</td> <td rowspan="13">DIN EN ISO: 15651-1:2012-09</td> </tr> <tr> <td>Emission of chemicals harmful to the environment and health</td> <td>Evaluated</td> </tr> <tr> <td colspan="3">Water tightness and air tightness</td></tr> <tr> <td>▪ Stability</td> <td>≤ 3,5 mm</td></tr> <tr> <td>▪ Volume loss</td> <td>≤ 10</td></tr> <tr> <td>▪ Tensile properties/edge modulus (elongation stress value)</td> <td>≥ 0,45 (+23° C) und ≥ 0,6 (-20 °C)</td></tr> <tr> <td>▪ Adhesion/expansion behaviour after exposure to heat, water & artificial light</td> <td>Performance not determined</td></tr> <tr> <td>▪ Elastic recovery</td> <td>≥ 80 %</td></tr> <tr> <td>▪ Tensile behaviour, i.e. Elongation under preload after immersion in water</td> <td>No failure</td></tr> <tr> <td>▪ Tensile behaviour under preload</td> <td>No failure</td></tr> <tr> <td>▪ Tensile strength</td> <td>No failure</td></tr> <tr> <td>Durability</td> <td>No failure</td></tr> <tr> <td>Microbiological growth</td> <td>2</td></tr> </tbody> </table>		Essential property	Performance	Harmonised technical specification	Fire behaviour	Class E	DIN EN ISO: 15651-1:2012-09	Emission of chemicals harmful to the environment and health	Evaluated	Water tightness and air tightness			▪ Stability	≤ 3,5 mm	▪ Volume loss	≤ 10	▪ Tensile properties/edge modulus (elongation stress value)	≥ 0,45 (+23° C) und ≥ 0,6 (-20 °C)	▪ Adhesion/expansion behaviour after exposure to heat, water & artificial light	Performance not determined	▪ Elastic recovery	≥ 80 %	▪ Tensile behaviour, i.e. Elongation under preload after immersion in water	No failure	▪ Tensile behaviour under preload	No failure	▪ Tensile strength	No failure	Durability	No failure	Microbiological growth	2
Essential property	Performance	Harmonised technical specification																															
Fire behaviour	Class E	DIN EN ISO: 15651-1:2012-09																															
Emission of chemicals harmful to the environment and health	Evaluated																																
Water tightness and air tightness																																	
▪ Stability	≤ 3,5 mm																																
▪ Volume loss	≤ 10																																
▪ Tensile properties/edge modulus (elongation stress value)	≥ 0,45 (+23° C) und ≥ 0,6 (-20 °C)																																
▪ Adhesion/expansion behaviour after exposure to heat, water & artificial light	Performance not determined																																
▪ Elastic recovery	≥ 80 %																																
▪ Tensile behaviour, i.e. Elongation under preload after immersion in water	No failure																																
▪ Tensile behaviour under preload	No failure																																
▪ Tensile strength	No failure																																
Durability	No failure																																
Microbiological growth	2																																

10. The performance of the product as per items 1 and 2 matches the declared performance in line with item 9 up to the expiry date printed on the packaging. The instructions for use (TDB, SDB) must be observed.

The manufacturer as per item 4 is solely responsible for authoring the Declaration of Performance.
Signed for and on behalf of the manufacturer by:



Kornelius Kurz, Managing Director