

1320 SCHUTZVLIES

Technical Data Sheet



1320 SCHUTZVLIES

Self-adhesive floor covering

1. Mechanical Properties

| | |
|---|---|
| Material | Non-woven fabric made of synthetic fibres |
| Upper face | With non-woven fabric |
| Underside | With self-adhesive film |
| Thickness | ~ 1.0 to 1.5 mm |
| Width | 100 cm |
| Roll length | 50 m |
| Carton | 100 linear m |
| Pallet unit | 1,050 linear m |
| Colour | White |
| Storage life (in sealed original package) | 6 months |

2. Properties

Ramsauer "SCHUTZVLIES 1320" with a very good self-adhesive film backing, high abrasion resistance and good slip resistance is designed for fast, crease-free laying. SCHUTZVLIES 1320 is pollutant-free, has a highly absorbent non-woven surface, is solvent-resistant and can be removed even after up to 3 months outdoors without leaving any residues.

3. Application

Self-adhesive protective non-woven for universal application on a variety of substrates, such as parquet and laminate floors, stairs, textile floors, ceramics, tiled floors, etc. Specially suited as a floor covering for building, painting and decorating work.

4. Work planning

The substrate must be permanently dry, free from dust and grease, and sufficiently tension- and compression-proof.

5. Processing

With the non-woven side facing up, lay out crease-free lengths with an overlap of approx. 10 cm. Watch out for potential tripping hazards and eliminate them if possible.

6. Safety instructions

Not a hazardous substance in the sense of the Ordinance on Hazardous Substances.

7. Application notes

"1320 SCHUTZVLIES" is not suitable for freshly laid floors, porous stone floors, natural stone floors, marble floors and clay tiles. Underfloor heating must be switched off, if installed. We recommend a test in an inconspicuous area before installation. Special attention must be paid in case of waxed, varnished wood and parquet floors as well as old, heavily stressed substrates.

The film can be removed even after up to 3 months outdoors without leaving any residues. When removing "SCHUTZVLIES 1320", make sure that this is done at an acute angle to the substrate. In the case of multiple use, pay attention to possible contamination, as this could possibly reduce the adhesive strength of the self-adhesive side.

8. Liability for defects

The information, in particular the suggestions for the processing and use of our products, is based on our knowledge and experience in normal use cases at the time of printing. Depending on the specific circumstances, in particular with regard to substrates, processing and environmental conditions, the results may differ from this information. Therefore the guarantee of a work result or a liability, for whatever legal reasons, can be justified neither from these references, nor from a verbal consultation, unless we are guilty of intent or gross negligence in this respect. Ramsauer guarantees that its products comply with the technical properties specified in the technical data sheets until the expiry date.

Product users must consult the latest technical data sheet, which can be requested from us. Our current General Terms and Conditions apply, which you can download at any time from our homepage at www.ramsauer.at.