



RAMSAUER®
DICHTSTOFFE

506 GLÄTTMITTEL SPEZIAL (SPECIAL SMOOTHER)

CHARACTERISTICS

Ready for use – not to be diluted

Serves for final smoothing of all Ramsauer silicone-, polyurethane- and hybrid sealants.

Ramsauer 506 GLÄTTMITTEL SPEZIAL modifies the surface tension of the sealants in such a way that the pasty compounds will be readily workable which cannot be achieved with water only.

Ramsauer 506 GLÄTTMITTEL SPEZIAL reacts neutrally and is suitable for any and all cross-linking systems including in particular our type 440 NATURSTEIN ("Natural Stone"). Ramsauer 506 GLÄTTMITTEL SPEZIAL does not cause any drying edges or spots on natural stone, and therefore it is highly recommended for this type of application.

PROCESSING

Shake before use. Spray small quantities of Ramsauer 506 GLÄTTMITTEL SPEZIAL onto the sealant requiring finishing touches directly from the bottle or by means of a spray bottle. Remove any excess material and smoothen the sealant surface by means of a spreader. In order to achieve neat joint edges cover edges with adhesive tape. Remove tape immediately after smoothing the sealant. Remove any smoother residues from the substrate immediately in order to avoid the formation of spots. Otherwise, the formation of spots/discolouration cannot be ruled out completely due to the specific characteristics of natural stone. In order to avoid contamination of the smoother with ingredients of the sealant it is recommended to use it only once. Avoid smoother pools on the sealant since this may cause the formation of water spots.

PACKAGING/STORAGE LIFE

1000ml spray bottles, 5 l cans

9 months (in a cool and dry place protected from frost)

ATTENTION!

Use fresh smoother only! Avoid silicone residues in the smoother. This product is not suitable for acrylic sealants on a dispersion basis. Using smoothers on highly sensitive types of natural stone may cause spots/discolouration which cannot be removed by means of conventional cleaners. In view of the wide range of possible influences and effects during processing and application we recommend to conduct project-

specific processing and/or application tests in any case. Do not use the product in large quantities and do not let it dry since dry residues may affect the visual appearance of the sealant surface. In case of glass, immediately remove any excess smoother or smoother flowing down. Otherwise, streaks will remain.

SAFETY ADVICE AND ADVICE FOR DISPOSAL

Consult the current EC Safety Data Sheet which is available at any time on our website at www.ramsauer.at.

LIABILITY FOR DEFECTS

The information provided including but not limited to the proposals for processing and using our products is based on our knowledge and experience, usually at the time of going into print. The results of work may deviate from this information depending on the specific circumstances, in particular with respect to substrates, processing and

environmental conditions. Therefore, neither this information nor any oral counselling shall constitute warranty or give rise to any liability on whatever legal ground for any specific result of work, unless we acted intentionally or by gross negligence. Ramsauer warrants that its products will have the technical characteristics according to the Technical Data Sheets up to

506 Glättmittel Spezial / Version: 01/15

Page:1

Supersedes version: 01/11

Ramsauer GmbH & Co KG, 4822 Bad Goisern/Hallstätter See, Sarstein 17, Austria

Phone: +43 (0)6135 8205-0, Fax: +43 (0)6135 8323 - Email: office@ramsauer.at - Internet: www.ramsauer.at





RAMSAUER®
DICHTSTOFFE

their expiry date.
Product users must consult the latest data sheet which is available upon request. Our current General Terms and

Conditions apply which are available for download on our website www.ramsauer.at.



QUALITY YOU CAN RELY ON

Ramsauer GmbH & Co KG, 4822 Bad Goisern/Hallstätter See, Sarstein 17, Austria

Phone: +43 (0)6135 8205-0, Fax: +43 (0)6135 8323 - Email: office@ramsauer.at - Internet: www.ramsauer.at